

DESCRIPTION**REMOTE FISH LOGGING UNIT**

5

FIELD OF THE INVENTION

The present invention relates generally to a system for electronically recording and exchanging information between a remote location and a central location, and more particularly to a remote logging device for electronically recording data relating to fishing conditions at a remote location and to a system for exchanging relevant information between such a remote device and a central repository.

15

BACKGROUND

In order to maximize their enjoyment and success at their sport, recreational fishing enthusiasts often would like to have information regarding fishing conditions in an area, especially before setting out on a fishing trip. For example, fishermen may consider trying something new, such as going to a new location, but may be reluctant to do so because of their inexperience with and lack of information regarding the new location. Thus, they may want to know, for example, at what locations fish are more actively biting, what species are likely to be encountered in an area, what bait is attracting more fish, at what depths fish are

being caught, what environmental conditions may enhance the likelihood of a successful outing, and the like.

Often, however, only limited information is available and only in limited quantities or distribution. For example, word-
5 of-mouth may provide some insight into fishing conditions in an area. However, such information may also involve "fish stories" with little accuracy or predictive value.

To improve the accuracy of information, some sports fishing enthusiasts may keep a personal log of their fishing activities.
10 For example, they may maintain written records of their past experiences and successes to provide them with some insight into future conditions at locations where they have fished before. However, such written records may omit useful details or may include inaccurate information, particularly if the records are
15 written after an outing. Past experiences in an area also may not always predict future encounters, particularly as conditions change with time. Further, because most logs are personal in nature, they may not be widely shared with others. Thus, individual fishermen, while having the benefit of their own logs,
20 generally may not have the combined insight available if they could pool their knowledge and experiences with other fishing enthusiasts.

Accordingly, it is believed that a system for more accurately recording and sharing relevant information on fishing

conditions, species populations, and/or natural resource demographic information would be useful.

SUMMARY OF THE INVENTION

The present invention is directed to a system for
5 electronically recording and/or collecting relevant information on fishing, hunting and other conditions at a number of locations, and to a method of exchanging information between an individual and a central repository storing such information.

In a preferred embodiment in accordance with the present
10 invention, a remote fish logging unit is provided for electronically recording information on fishing conditions at a particular location. The remote unit is a portable data gathering device that users may take along to a location where they fish. The remote unit includes a set of sensors for
15 measuring relevant physical properties or environmental conditions, a storage device for temporarily storing data measured by the sensors, and a display, together allowing the user to measure, store, and/or review data of relevant conditions at the location when a fish or other specimen is caught. For
20 example, the device may include a scale for weighing the fish, a retractable cable for measuring the length of the fish, atmospheric sensors for measuring air temperature and pressure, water sensors for measuring water temperature and pH, and a global positioning system (GPS) for providing an accurate

longitude and latitude of the location. The remote unit may also include manual input mechanisms, such as a touch screen, an arrow pad, or keypad, for providing additional information related to the conditions of the catch.

- 5 The remote unit includes a central processor which receives signals from the sensors and measuring devices proportional to the properties being measured, converts the signals into corresponding data values, and temporarily stores the data in the remote unit's memory. As individual fish are caught, the remote
- 10 unit may be operated in a concurrent mode to record each catch. The processor may be directed to store data measured by the sensors related to the physical properties of the fish and/or the environmental conditions at the time. The processor may also store the time, date and geographic location of the catch.
- 15 Additional information related to the fishing conditions may be entered manually and stored along with the corresponding measured data. Alternatively, a summary of information related to a number of fish caught may be entered at one time, for example at the end of a day's fishing, by operating the remote unit in a
- 20 batch mode.

Once data is recorded using the remote unit, it may be temporarily stored in the unit's memory and may be recovered later to create a personal log of the user's fishing activities, for example using a personal computer. Alternatively, the remote

unit may be used to exchange information with a central repository, such as a network server, either through a connection with a personal computer or from its remote data-gathering location.

5 To accomplish remote data exchanging, the remote unit may include a transmitter which sends a signal including the data stored in the unit's memory. The signal is received by a base station or is otherwise relayed to a network server. The network server includes a processor which adds the data from the signal
10 to a database on fishing conditions previously received from other remote units and stored in the server's memory. The information may be sorted in a variety of ways, such as by geographic location, allowing particular data to be extracted by subscribers to the network.

15 The remote unit may also be used to access data from the network server directly from its remote location. The transmitter in the remote unit may send a signal including a selected location for which the user wants information, for example his present location. The signal may be relayed to the
20 network server, which extracts information for the selected location from its database. A signal then may be sent back to the remote unit including the extracted data, and a receiver in the remote unit may receive the signal. The processor may

temporarily store the data from the signal in memory, allowing the user to review the information on the remote unit's display.

Accordingly, an object of the present invention is to provide a device for electronically collecting and recording data on fishing, hunting or other conditions at a remote location.

It is also an object to provide a system for storing and sharing information related to fishing conditions accumulated from individual fishing or hunting experiences.

It is still another object of the present invention to provide an improved system and method for tracking and/or managing migrational natural resources such as fish and game.

Other objects and features of the present invention will become apparent from consideration of the following description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a remote unit in accordance with the present invention.

FIG. 2 is a schematic of a system for sharing information related to fishing conditions between a remote unit and a central network server.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In one innovative aspect, the present invention is directed to a portable data-gathering device, which users may take along to a location where they fish or hunt, and which may be used for

electronically recording relevant information related to their activities and/or for exchanging relevant information with a central repository, such as a network server. A recording device in accordance with the present invention is generally a portable

5 hand-held device having a casing that contains all of the unit's sensors and electronic components. The casing is preferably relatively small and lightweight such that the device may be held easily by a user, for example using only one hand. The casing may be manufactured from plastic, metal, composites or other

10 materials capable of providing a substantially water proof seal and/or a durable package for protecting the internal components. In addition, the casing material itself, or one or more interior chambers within the casing, may provide sufficient buoyancy to allow the device to float, for example if it is accidentally

15 dropped in water. If desired, the casing (or chambers therein) may be filled with an inert gas to impede corrosion and minimize fogging of any display screen(s).

The recording device may include one or more sensors, transducers or input mechanisms for measuring environmental

20 conditions, specimen data and/or electronically recording information related to fishing condition from the user's remote location. The sensors may include conventional transducers capable of providing an output proportional to a physical property or condition being measured, preferably an electrical

signal proportional to the property, as will be appreciated by those skilled in the art. The signals may be converted by processor circuitry in the recording device to provide a data value which may be stored temporarily in memory circuitry. The
5 memory circuit may be part of the processor itself or may be provided as a discrete component within the recording device.

The recording device may also include one or more input mechanisms for manually recording additional conditions and data that the user may want to record, such as a touch screen, keypad,
10 or the like, and may also include a display screen, such as a conventional LCD, LED, TFT, color diode or fluorescent screen. A processor may be connected to the input mechanisms and the display screen to provide an interface between the user and the recording device, as will be appreciated by those skilled in the
15 art. For example, menus may be displayed on the screen, and the user may select options from the menus using the input mechanisms, for example to activate the recording device, to enter additional data, and/or to access data or information stored in the memory of the recording device.

20 Turning now to the drawings, FIG. 1 shows a preferred embodiment of a remote fish logging unit 10 in accordance with the present invention. The remote unit 10 includes sensors 30 for measuring atmospheric conditions at the location, such as a thermocouple or thermometer for measuring air temperature and/or

10 a barometer for measuring atmospheric pressure. The remote unit
10 also includes a probe 36 for measuring water conditions at the
location, such as a thermocouple or thermometer for measuring
temperature and/or a pH level detector. Preferably, the probe 36
5 is mounted on the end 34 of a retractable cable 32 that may be
drawn out from the casing 20 to facilitate contact with a body of
water at the location. For example, the cable 32 may be a long,
substantially flexible wire wound inside the casing 20 on a
spring-retractable spool (not shown), or the cable 32 may be a
10 long telescoping member with the probe 36 located on its end.
The cable 32 is pulled out of the casing 20, possibly
automatically locking as a length is withdrawn, until a section
of cable 32 is extended that allows the probe 36 to reach the
water being measured. Alternatively, the cable 32 may be
15 manually unwound from the casing, for example by an external
handle (not shown) connected to the internal spool. After
obtaining the desired data, the cable 32 is retracted, for
example using a mechanical release and a biased spring for
automatically retracting, or by manually rewinding the cable 32.
20 In addition, the remote unit 10 includes measuring devices
for obtaining physical data on a fish or other specimen caught at
the location, such as a scale 38 from which a fish (not shown)
may be hung to measure its weight. In addition, a device for
measuring the length of a fish may be included (not shown). For

example, the cable 32 may include length demarcations proceeding incrementally from its end 34, such that a section of the cable 32 may be extended from the casing 20 to expose the demarcations and allow the length of a fish to be measured. The length may be
5 measured automatically by the remote unit 10 based upon the length of the cable 32 extended, or the length may be observed visually by the user and input manually.

The remote unit 10 also includes a number of input mechanisms for manually entering information, such as a touch
10 screen 40. The touch screen 40 has a preset menu from which the user may select options, or it may have a plurality of menus which may be selectively activated and accessed by the user. For example as shown, the touch screen 40 may include images of species of fish from which the user may select a species by
15 pressing the appropriate portion of the touch screen 40. Alternatively, the available menus may include bait type used to catch a fish, depth at which a fish is caught, or other parameters which generally only have a limited number of selectable options.

20 The remote unit 10 also includes a control panel 44 for inputting additional data, and/or for controlling the operation of the remote unit 10. For example, the panel 44 may include an arrow pad 46 that allows the user to toggle between menus displayed on the screen 42, to enter additional data or comments,

or to review information stored in the memory of the remote unit 10. In addition, the remote unit 10 includes an entry button 48 that may be depressed, for example by the user's thumb, to control the remote unit's processor, or to indicate to the processor to electronically record a property measured by a selected sensor.

Additional electronic components (not shown) are also contained within the casing 20 of the remote unit 10, such as processor circuitry, memory circuitry, a global positioning system (GPS), and possibly communications circuitry (cellular, VHF, shortwave etc.). The casing 20 also holds a power source (not shown), such as conventional replaceable or rechargeable batteries, for providing power to operate the remote unit 10.

For example, the remote unit 10 includes a processor (not shown) for receiving the signals from the sensors and measurement devices, and for converting each signal into a data value. The processor temporarily stores the values in memory (not shown). Clock circuitry may be provided, either as part of the processor or as a separate internal component, which the processor may access to store the time and date when data is recorded.

In addition, the remote unit 10 may also be provided with communications circuitry (not shown), which is also generally controlled by the processor, for transferring the recorded data to a mass memory storage device external of the remote unit 10.

For example, a data port 50 is provided in the casing 20 for transferring data via a wire connection with the processor, such as between the unit's memory and a personal computer (not shown). Alternatively, wireless communication may be used to transfer

5 data between the remote unit 10 and a network server (not shown), for example using a null modem, serial approach, wireless radio, or IR transfer techniques that are well known in the art. The remote unit 10 preferably includes a transmitter (not shown) for sending a data or inquiry signal to a base station which relays

10 the data to the server, and/or a receiver (not shown) for receiving a data signal from the server, preferably using conventional cellular telecommunications. An antenna 52 is mounted on the casing 20 that is connected to the communications circuitry and/or the processor for transmitting and/or receiving

15 signals between the remote unit 10 and the base station.

If provided with a transmitter/receiver, the remote unit 10 preferably also includes a global positioning system (GPS) for determining the specific geographic location of the user, as will be appreciated by those skilled in the art. Thus, the processor

20 may request and store GPS data in the unit's memory when other data is recorded. Alternatively, the processor may direct the base station to determine the location of the remote unit 10 when data is relayed through the base station to the server.

When individual fish are caught, the operation of the remote unit 10 may proceed as follows, by operating the remote unit 10 in a concurrent mode. The remote unit 10 is turned on (if not already on), and may be used as a GPS to obtain geographic information on the remote unit's location. When a fish or other specimen is caught, the user may record the specimen data on the fish. For example, the species of the fish may be selected from the touch screen 40, and the fish hung on the scale 38 to measure its weight. The cable 32 may be drawn out, and the length of the fish measured (and entered manually if not electronically measured).

The processor may include software to assist the user at this point in deciding whether to keep a fish whose specimen data has been recorded. Data on a set of species may be permanently stored within the processor's memory, may be downloaded before the remote unit 10 is taken out to a location, for example from a personal computer through the data port 50, or may be received from a network server using the remote data exchange process described below. The stored data on the selected species is cross-referenced with the specimen data (e.g. the weight and length) to determine whether the fish is large enough to keep. The remote unit 10 may then warn the user that the specimen does not qualify as a keeper, whereupon the user may opt to abandon the data and cancel the remainder of the data recording process.

006907 4303460

If the remote unit 10 indicates that the fish is acceptable (or the user opts to override the warning), the specimen data may be stored in memory. The processor may automatically store the time and date of the catch, the location of the unit, or the user
5 may enter such information manually. The processor may obtain atmospheric conditions from the sensors 30, either automatically or at the user's command, which may be stored along with the corresponding specimen data. The probe 36 may be extended and directed into the body of water from which the fish was caught,
10 and water condition data may be added to that already recorded. The processor may request the user to provide additional details, such as whether the specimen has a migratory tag, what the qualitative weather conditions are, and optionally may allow the user to input any additional personal notes or comments desired
15 regarding the circumstances of the catch. This process may be repeated each time a fish is caught at the location, and the processor may cumulatively record and store the information in memory for later retrieval or transfer.

Alternatively, the remote unit 10 may be operated in a batch
20 mode, allowing the user to input as much data as desired at one time. For example, if a user does not have time to enter data as each specimen is caught, the data may be recorded manually and input into the remote unit 10 at the end of a session, or the

specimen data on all of the fish caught may be measured at one time.

In addition, a simpler embodiment of a remote unit may be used for such batch mode operations. For example, a unit without
5 environmental sensors may be used if such environmental information may not be needed, or may be measured and entered manually. Alternatively, the unit may not have measuring devices for obtaining specimen data, and this information may be recorded and entered manually. Generally, however, an embodiment such as
10 the remote unit 10 described above which includes all of the sensors described is preferred, as it allows direct data recording with the remote unit 10 with substantially little risk of data becoming lost or being recorded incorrectly.

Subsequent to storing data in the unit's memory at a remote
15 location, the remote unit 10 may be used to transfer the data, for example, to a personal computer for creating a personal log of the user's ongoing fishing activities. A cable may be connected between the data port 50 on the remote unit 10 and a personal computer (not shown). The remote unit 10 may be
20 directed to transfer the data to the personal computer, or the personal computer may include a processor to control the remote unit 10 and extract the data from its memory. The personal computer may store the data indefinitely in its memory to create a personal log for the user and/or may transfer the data to a

network server comprising a centralized database, for example, using a modem connection. If desired, each remote unit 10 may be registered to a particular user or associated with a unique identification code to enable the network server and central
5 database to track the activity of individual remote units 10. In such an embodiment, the remote units 10 may also be used to provide rescue personnel with the last known location of, for example, a fishing vessel or hunting group.

Alternatively, data may be transferred directly from the
10 remote location to a network server comprising a central database compiled from such remote units, for subsequent use by other remote unit users and/or network subscribers. As shown in FIG. 2, a remote unit 10 may be taken to a remote location 100, such as on or adjacent a body of water 102 where the user is fishing
15 or otherwise obtaining specimens. The transmitter/receiver of the remote unit 10 may be used as a GPS to provide the geographic location 100 of the remote unit 10, such as the longitude 104 and latitude 106. Environmental conditions, specimen data and other relevant information may be electronically recorded at the
20 location 100 as desired, stored in the unit's memory, and prepared for transfer by the unit's processor. The remote unit 10 may send a signal to initiate contact with a base station 110, and may send a data signal 120 to the base station 110 that includes a summary of the data stored in the remote unit 10. The

base station 110 may then relay the data to a network server 120 designed as a central repository for such data. For example, the remote unit 10 may communicate with the network server 120 using conventional cellular telecommunications.

5 The network server 120 includes processor circuitry (not shown) and memory circuitry (not shown) for collecting and storing data received from the remote unit 10 and other similar units, that is to create a database of retrievable information related to fishing conditions. The data from the data signal
10 relayed through the base station 110 may be stored in the server's memory. The server's processor may add the data to a database of information previously received from other remote units and stored in the server's memory.

Remote unit users or subscribers authorized to access the
15 database may contact the network server 120 to review data, for example in anticipation of a fishing trip to a selected location. The subscriber may select a location, the network server 120 may extract information on the selected location from the database, and the subscriber may review the data compiled regarding that
20 location. In addition, statistics based upon the data stored in the server 120 may be used to track and/or manage migratory natural resources by providing sample data indicative of the number and location of the species comprising the resource at a given point in time or over a selected period of time.

Alternatively, a remote unit 10 may be used to access the database directly from a selected location, such as from the remote location where a user is fishing. The remote unit 10 may contact a base station 110, providing access to the network server 120. The remote unit 10 may send an inquiry signal, identifying a selected location, such as the unit's location (or optionally other locations if desired). The server 120 may then extract the previously compiled data for the selected location from the database, relay the data to the base station 110, which may then transmit a data signal to the remote unit 10. The remote unit 10 may store the data in its memory, and the user may then review the data on the selected location on the display screen 42, thereby allowing the user to make decisions about where to fish, what bait to use, whether existing weather conditions are suited for fishing, etc. based upon the information received.

Alternatively, if a user does not wish to share the data acquired using their remote unit, they may choose to store the data only in their personal log. As data is compiled in their log over time, the user may access the information at later dates to decide where to fish based on current weather conditions, what bait to use to increase success, etc.

The remote unit and database system described above may be particularly useful for recreational fishing enthusiasts. Such

users may use the remote units to record and share information with each other to mutually improve their enjoyment and success. Professional and commercial users may also use the system to track the movement of fish, for example to predict the location of schools of fish in the open seas. Government agencies or conservation groups may use the system to monitor the migration and rate of removal of fish or other migratory natural resources, thus providing a more sophisticated method of resource management, particularly if tagging information is recorded by the remote units and included in the server's database.

In an alternative embodiment, the remote unit may be substantially permanently or removably mounted, for example, on a vessel to serve as a logging instrument of the vessel's fishing activities. The remote unit may include sensors and measuring devices similar to those described above, or may receive information from other existing systems on the vessel, such as a GPS system for providing the vessel's location. Passengers and/or crew on the vessel may record information on fish caught and/or may access the network server to review conditions in the area. In addition to information related to fishing conditions, the remote unit may be used as a vessel log for recording information on fuel usage, passengers on board, and the like.

In a further alternative embodiment, the remote unit and database system may be used to electronically record and/or

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

While the invention is susceptible to various modifications, and alternative forms, specific examples thereof have been shown in the drawings and are herein described in detail. It should be understood, however, that the invention is not to be limited to the particular forms or methods disclosed, but to the contrary, the invention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the appended claims.